

SOMATA




TAVA 200

VACUUM DRUM




The Vacuum Drum works like a vacuum chamber and is a ready-to-install module for integration in filling systems as well as for vacuum drum change in dosing systems.

for 200 l drums



CASTING



GLUING

TAVA 200

VACUUM DRUM

The vacuum drum works like a vacuum chamber and is a ready-to-install module for integration in filling systems as well as for vacuum drum change in dosing systems. Developed and patented by the TARTLER GROUP, it is used to prevent air inclusions during material filling and to make the drum change of 200 l lidded drums absolutely safe for the operator and process.



Material filling under vacuum (TAVA F)

- ▶ For drum filling at the material manufacturer
- ▶ For material preparation at the end customer, before processing
- ▶ Semi-automatic degassing station for air-free filling of 50 and 200 litre drums, which can be used flexibly for various pasty and highly viscous media

Benefits of drums filled without air

- ▶ Guarantee that the optimally filled drums do not contain any air inclusions and that further processing is reliable
- ▶ Increased storage stability, as contamination with air/humidity is no longer possible



Process-reliable drum change (TAVA D)

- ▶ Easy and safe change of component drums without the risk of introducing harmful air into the system or process
- ▶ Fully automated degassing or evacuation station with vacuum drum for taking up, pumping off and venting the lidded drums

Benefits of using the TAVA D means

- ▶ No air introduction into the dosing and mixing unit during routine drum change
- ▶ No risk of splashing (no contamination of the operator with material)
- ▶ No material loss
- ▶ No monitoring / permanent presence of the operator necessary
- ▶ Any remaining material in the inliner can be added without affecting the material in the following drum



Application and info videos can be found on our international YouTube channel: <https://yt.vu/+somata>

TECHNICAL DATA

Vacuum pump	25 m ³ /h, ultimate pressure 0.1 mbar
Tank	200 l drum (possible with and without Inliner)
Equipment	<ul style="list-style-type: none">▶ vacuum drum with cover▶ connection for material supply▶ sight glass▶ level control
Optional additional equipment	<ul style="list-style-type: none">▶ Colour of the drum on customer request / VA▶ Drum lifter▶ Scale▶ further special equipment possible

SOMATA



SOMATA GmbH

Relystr. 48
D-64720 Michelstadt

Phone: +49 (0) 6061 96 72-0
E-Mail: info@somata-gmbh.com
Web: www.somata-gmbh.com